

ステンレス織金網 参考規格表(1.5~11Mesh)

Mesh	線径 (mm)	開き目 (mm)	空間率 (%)
1.5	2.0	14.93	77.8 %
	1.6	15.33	82.0 %
2.	2.0	10.7	71.0 %
	1.9	10.8	72.3 %
	1.6	11.1	76.4 %
	1.5	11.2	77.8 %
	1.2	11.5	82.0 %
2.2	1.6	9.95	74.2 %
2.5	2.0	8.16	64.5 %
	1.9	8.26	66.1 %
	1.6	8.56	71.0 %
	1.5	8.66	72.7 %
	1.2	8.96	77.8 %
	1.1	9.06	79.5 %
	1.0	9.16	81.3 %
3.	2.0	6.47	58.3 %
	1.9	6.57	60.2 %
	1.6	6.87	65.8 %
	1.5	6.97	67.7 %
	1.2	7.27	73.7 %
	1.1	7.37	75.7 %
3.2	2.0	5.94	56.0 %
	1.9	6.04	57.9 %
	1.5	6.44	65.8 %
	1.1	6.84	74.2 %
	1.0	6.94	76.4 %
3.5	1.9	5.36	54.5 %
	1.6	5.66	60.8 %
	1.5	5.76	62.9 %
	1.2	6.06	69.7 %
	1.1	6.16	72.0 %
4.	1.0	6.26	74.3 %
	2.0	4.35	46.9 %
	1.9	4.45	49.1 %
	1.6	4.75	56.0 %
	1.5	4.85	58.3 %
	1.2	5.15	65.8 %
	1.1	5.25	68.4 %
	1.0	5.35	71.0 %
	0.95	5.40	72.3 %
	0.9	5.45	73.7 %
0.83	5.52	75.6 %	
0.8	5.55	76.4 %	

Mesh	線径 (mm)	開き目 (mm)	空間率 (%)
4.2	1.0	5.05	69.7 %
4.5	1.6	4.04	51.3 %
	1.5	4.14	53.9 %
	1.2	4.44	62.0 %
	1.1	4.54	64.8 %
5.	1.9	3.18	39.2 %
	1.6	3.48	46.9 %
	1.5	3.58	49.7 %
	1.2	3.88	58.3 %
	1.1	3.98	61.4 %
	1.0	4.08	64.5 %
	0.95	4.13	66.1 %
	0.9	4.18	67.7 %
	0.83	4.25	70.0 %
	0.8	4.28	71.0 %
	0.75	4.33	72.7 %
5.5	0.7	4.38	74.3 %
	1.6	3.02	42.7 %
	1.5	3.12	45.6 %
	1.2	3.42	54.8 %
6.	1.1	3.52	58.0 %
	1.6	2.63	38.7 %
	1.5	2.73	41.7 %
	1.2	3.03	51.3 %
	1.1	3.13	54.8 %
	1.0	3.23	58.3 %
	0.95	3.28	60.2 %
	0.9	3.33	62.0 %
	0.8	3.43	65.8 %
	0.75	3.48	67.7 %
6.5	0.7	3.53	69.7 %
	0.65	3.58	71.6 %
	0.6	3.63	73.7 %
	1.1	2.81	51.6 %
	0.95	2.96	57.3 %
	0.9	3.01	59.2 %
	0.8	3.11	63.2 %
	0.75	3.16	65.3 %
	0.7	3.21	67.4 %
	0.65	3.26	69.5 %
6.5	0.6	3.31	71.6 %
	0.57	3.34	73.0 %

Mesh	線径 (mm)	開き目 (mm)	空間率 (%)
7.	1.1	2.53	48.6 %
	1.0	2.63	52.5 %
	0.8	2.83	60.8 %
	0.75	2.88	62.9 %
	0.65	2.98	67.4 %
	0.6	3.03	69.7 %
	0.57	3.06	71.1 %
7.5	1.0	2.39	49.7 %
8.	1.2	1.98	38.7 %
	1.1	2.08	42.7 %
	1.0	2.18	46.9 %
	0.95	2.23	49.1 %
	0.9	2.28	51.3 %
	0.8	2.38	56.0 %
	0.75	2.43	58.3 %
	0.7	2.48	60.8 %
	0.65	2.53	63.2 %
	0.6	2.58	65.8 %
	0.57	2.61	67.3 %
9.	0.53	2.65	69.4 %
	0.5	2.68	71.0 %
	0.47	2.71	72.6 %
	0.45	2.73	73.7 %
	1.1	1.72	37.2 %
9.	0.9	1.92	46.4 %
	0.8	2.02	51.3 %
	0.65	2.17	59.2 %
10.	1.2	1.34	27.8 %
	1.1	1.44	32.1 %
	1.0	1.54	36.8 %
	0.95	1.59	39.2 %
	0.9	1.64	41.7 %
	0.8	1.74	46.9 %
	0.75	1.79	49.7 %
	0.7	1.84	52.5 %
	0.65	1.89	55.4 %
	0.6	1.94	58.3 %
	0.57	1.97	60.2 %
10.	0.53	2.01	62.6 %
	0.5	2.04	64.5 %
	0.47	2.07	66.4 %
	0.45	2.09	67.7 %
	0.43	2.11	69.0 %
	0.4	2.14	71.0 %
	0.57	1.74	56.7 %

Mesh: 1インチ(25.4mm)間にある網目の数
定尺: 幅1000mm×30m巻

ステンレス織金網 参考規格表(12~635Mesh)

Mesh	線径 (mm)	開き目 (mm)	空間率 (%)
12.	1.0	1.12	27.8 %
	0.95	1.17	30.4 %
	0.9	1.22	33.0 %
	0.8	1.32	38.7 %
	0.75	1.37	41.7 %
	0.7	1.42	44.8 %
	0.65	1.47	48.0 %
	0.6	1.52	51.3 %
	0.57	1.55	53.4 %
	0.5	1.62	58.3 %
	0.47	1.65	60.5 %
	0.45	1.67	62.0 %
	0.43	1.69	63.5 %
	0.4	1.72	65.8 %
0.37	1.75	68.1 %	
0.34	1.78	70.5 %	
14.	0.8	1.01	31.3 %
	0.75	1.06	34.4 %
	0.7	1.11	37.7 %
	0.65	1.16	41.2 %
	0.6	1.21	44.8 %
	0.57	1.24	47.0 %
	0.5	1.31	52.5 %
	0.47	1.34	54.9 %
	0.45	1.36	56.5 %
	0.43	1.38	58.2 %
	0.4	1.41	60.8 %
	0.37	1.44	63.4 %
	0.34	1.47	66.0 %
	0.29	1.52	70.6 %
16.	0.8	0.79	24.6 %
	0.7	0.89	31.3 %
	0.65	0.94	34.9 %
	0.6	0.99	38.7 %
	0.57	1.02	41.1 %
	0.5	1.09	46.9 %
	0.47	1.12	49.6 %
	0.45	1.14	51.3 %
	0.43	1.16	53.2 %
	0.4	1.19	56.0 %
	0.37	1.22	58.8 %
	0.34	1.25	61.8 %
	0.29	1.30	66.8 %
	0.25	1.34	71.0 %

Mesh	線径 (mm)	開き目 (mm)	空間率 (%)	
18.	0.6	0.81	33.0 %	
	0.57	0.84	35.5 %	
	0.5	0.91	41.7 %	
	0.47	0.94	44.5 %	
	0.45	0.96	46.4 %	
	0.43	0.98	48.3 %	
	0.4	1.01	51.3 %	
	0.37	1.04	54.4 %	
	0.34	1.07	57.6 %	
	0.29	1.12	63.1 %	
	0.25	1.16	67.7 %	
	20.	0.57	0.70	30.4 %
		0.5	0.77	36.8 %
		0.47	0.80	39.7 %
0.45		0.82	41.7 %	
0.43		0.84	43.7 %	
0.4		0.87	46.9 %	
0.37		0.90	50.2 %	
0.34		0.93	53.6 %	
0.29		0.98	59.5 %	
0.25		1.02	64.5 %	
22.	0.45	0.70	37.2 %	
24.	0.45	0.61	33.0 %	
	0.4	0.66	38.7 %	
	0.37	0.69	42.3 %	
	0.34	0.72	46.1 %	
	0.29	0.77	52.7 %	
	0.25	0.81	58.3 %	
	0.22	0.84	62.7 %	
	28.	0.29	0.62	46.3 %
30.	0.4	0.45	27.8 %	
	0.34	0.51	35.8 %	
	0.29	0.56	43.2 %	
	0.25	0.60	49.7 %	
	0.22	0.63	54.8 %	
	0.2	0.65	58.3 %	
	0.18	0.67	62.0 %	
	32.	0.29	0.50	40.3 %
0.25		0.54	46.9 %	
0.22		0.57	52.2 %	
35.	0.2	0.59	56.0 %	
	0.25	0.48	43.0 %	
	0.22	0.51	48.6 %	

Mesh	線径 (mm)	開き目 (mm)	空間率 (%)
40.	0.29	0.35	29.5 %
	0.25	0.39	36.8 %
	0.23	0.41	40.7 %
	0.22	0.42	42.7 %
	0.2	0.44	46.9 %
	0.18	0.46	51.3 %
	0.16	0.48	56.0 %
	0.14	0.50	60.8 %
50.	0.23	0.28	29.9 %
	0.22	0.29	32.1 %
	0.2	0.31	36.8 %
	0.18	0.33	41.7 %
60.	0.16	0.35	46.9 %
	0.14	0.37	52.5 %
	0.18	0.24	33.0 %
70.	0.16	0.26	38.7 %
	0.14	0.28	44.8 %
	0.12	0.30	51.3 %
	0.16	0.20	31.3 %
80.	0.14	0.22	37.7 %
	0.12	0.24	44.8 %
90.	0.14	0.18	31.3 %
100.	0.12	0.20	38.7 %
120.	0.1	0.18	41.7 %
150.	0.1	0.154	36.8 %
165.	0.08	0.132	38.7 %
180.	0.06	0.109	41.7 %
200.	0.05	0.104	45.6 %
250.	0.05	0.091	41.7 %
270.	0.05	0.0770	36.8 %
300.	0.04	0.0616	36.8 %
325.	0.04	0.0541	33.0 %
350.	0.04	0.0447	27.8 %
400.	0.035	0.0432	30.5 %
500.	0.035	0.0376	26.8 %
635.	0.03	0.0335	27.8 %
	0.025	0.0258	25.8 %
	0.02	0.0200	25.0 %

(綾織)
(綾織)
(綾織)
(綾織)
(綾織)
(綾織)
(綾織)
(綾織)

Mesh: 1インチ(25.4mm)間にある網目の数
定尺: 幅1000mm×30m巻

亜鉛引織金網 参考規格表(1.6~60Mesh)

Mesh	線径 (mm)	開き目 (mm)	空間率 (%)
1.6	2.0	13.88	76.4 %
	1.6	14.28	80.9 %
	1.5	14.38	82.0 %
	1.4	14.48	83.1 %
2.	2.0	10.7	71.0 %
	1.6	11.1	76.4 %
	1.5	11.2	77.8 %
	1.4	11.3	79.2 %
2.5	2.0	8.16	64.5 %
	1.6	8.56	71.0 %
	1.5	8.66	72.7 %
	1.4	8.76	74.3 %
	1.2	8.96	77.8 %
	1.1	9.06	79.5 %
3.	2.0	6.47	58.3 %
	1.6	6.87	65.8 %
	1.5	6.97	67.7 %
	1.4	7.07	69.7 %
	1.2	7.27	73.7 %
	1.1	7.37	75.7 %
3.2	2.0	5.94	56.0 %
	1.6	6.34	63.8 %
	1.5	6.44	65.8 %
	1.4	6.54	67.9 %
	1.2	6.74	72.1 %
	1.1	6.84	74.2 %
	1.0	6.94	76.4 %
	0.9	7.04	78.6 %
3.5	1.1	6.16	72.0 %
4.	2.0	4.35	46.9 %
	1.6	4.75	56.0 %
	1.5	4.85	58.3 %
	1.4	4.95	60.8 %
	1.2	5.15	65.8 %
	1.1	5.25	68.4 %
	1.0	5.35	71.0 %
	0.9	5.45	73.7 %
	0.8	5.55	76.4 %
	0.7	5.65	79.2 %
	0.63	5.72	81.1 %
4.5	1.6	4.04	51.3 %
	1.4	4.24	56.5 %

Mesh: 1インチ(25.4mm)間にある網目の数
定尺: 幅910mm×30m巻

Mesh	線径 (mm)	開き目 (mm)	空間率 (%)
5.	2.0	3.08	36.8 %
	1.6	3.48	46.9 %
	1.4	3.68	52.5 %
	1.2	3.88	58.3 %
	1.1	3.98	61.4 %
	1.0	4.08	64.5 %
	0.9	4.18	67.7 %
	0.8	4.28	71.0 %
	0.7	4.38	74.3 %
	0.63	4.45	76.7 %
5.5	1.6	3.02	42.7 %
	1.4	3.22	48.6 %
6.	1.6	2.63	38.7 %
	1.4	2.83	44.8 %
	1.2	3.03	51.3 %
	1.1	3.13	54.8 %
	1.0	3.23	58.3 %
	0.9	3.33	62.0 %
	0.8	3.43	65.8 %
	0.7	3.53	69.7 %
6.5	1.4	2.51	41.2 %
	1.2	2.71	48.0 %
	1.1	2.81	51.6 %
	1.0	2.91	55.4 %
	0.8	3.11	63.3 %
	0.63	3.28	70.4 %
	0.55	3.36	73.8 %
	8.	1.2	1.98
1.0		2.18	46.9 %
0.9		2.28	51.3 %
0.8		2.38	56.0 %
0.7		2.48	60.8 %
0.63		2.55	64.3 %
0.55		2.63	68.4 %
0.5		2.68	71.0 %
10.	0.45	2.73	73.7 %
	1.2	1.34	27.8 %
	1.0	1.54	36.8 %
	0.9	1.64	41.7 %
	0.8	1.74	46.9 %
	0.7	1.84	52.5 %
	0.63	1.91	56.6 %
	0.55	1.99	61.4 %
	0.5	2.04	64.5 %
	0.45	2.09	67.7 %
0.4	2.14	71.0 %	

Mesh	線径 (mm)	開き目 (mm)	空間率 (%)
11.	0.8	1.51	42.7 %
	0.55	1.76	58.0 %
	0.45	1.86	64.8 %
	0.34	1.97	72.7 %
12.	0.9	1.22	33.1 %
	0.8	1.32	38.7 %
	0.7	1.42	44.8 %
	0.63	1.49	49.4 %
	0.55	1.57	54.8 %
	0.5	1.62	58.4 %
	0.45	1.67	62.0 %
	0.4	1.72	65.8 %
	0.34	1.78	70.5 %
	0.28	1.84	75.3 %
14.	0.8	1.01	31.2 %
	0.63	1.18	42.6 %
	0.55	1.26	48.5 %
	0.5	1.31	52.5 %
	0.45	1.36	56.5 %
	0.4	1.41	60.7 %
	0.34	1.47	66.0 %
	0.28	1.53	71.5 %
16.	0.55	1.04	42.8 %
	0.5	1.09	47.0 %
	0.45	1.14	51.4 %
	0.4	1.19	56.0 %
	0.34	1.25	61.8 %
	0.28	1.31	67.9 %
18.	0.34	1.07	57.6 %
	0.28	1.13	64.2 %
20.	0.5	0.77	36.8 %
	0.45	0.82	41.7 %
	0.4	0.87	46.9 %
	0.34	0.93	53.6 %
24.	0.28	0.99	60.8 %
	0.45	0.61	33.0 %
	0.4	0.66	38.7 %
	0.34	0.72	46.0 %
30.	0.28	0.78	54.0 %
	0.23	0.83	61.2 %
	0.28	0.57	44.9 %
	0.23	0.62	53.1 %
32.	0.23	0.56	50.5 %
40.	0.23	0.41	40.7 %
50.	0.23	0.28	30.0 %
60.	0.18	0.24	33.0 %